




KS-21

3 db VHF fiberglass antenna 1,0 m (3.3') length

 The KS-21 is the perfect antenna for small boats and RIBs. With only 100 cm length it guarantees the same performance of a 150 cm length VHF antenna. It's built with a 1,4 mm thick fiberglass whip that gets fully foam injected with the special Scout 100% waterproof technique, and it's ice white colored with high gloss anti-UV filter to prevent color deterioration. The 5m top performance RG-58 MIL cable completes the characteristics of the KS-21, an antenna that is perfect for its design and construction. It is supplied with 1 PL-259 connector to complete the installation on board. A perfect antenna for its design and construction.

 La nuova KS-21 è l'antenna ideale per le piccole imbarcazioni e per i gommoni. In soli 100 cm di lunghezza garantisce le medesime prestazioni delle antenne lunghe 150 cm. Costruita con un corpo in vetroresina con spessore di 1,4 mm interamente riempito di poliuretano con la speciale tecnica Scout 100% waterproof, e verniciata con tonalità bianco ghiaccio e filtro anti-UV per prevenire il deterioramento del colore ai raggi solari. Viene fornita con 5m di cavo RG-58 top performance a norme militari e un connettore PL-259 per completare l'installazione a bordo. Una antenna perfetta per concezione e costruzione.

 Die neue KS-21 ist die perfekte Antenne für kleine Boote und RIBs. Mit nur 100 cm garantiert sie jedoch die gleiche Leistung, wie die 150 cm UKW Antennen. Spezielle Farbe mit Anti - UV Filter und 100% WATERPROOF. Es hat einen 1,4mm Glasfaser Stab, der mit der speziellen 100% Waterproof Technik komplett schaumgefüllt ist, zusätzlich einen Hochglanz Anti UV- Filter, der die Farbe schützt. Die Antenne wird mit 5 m RG-58 MIL-Kabel und 1 PL-259-Stecker geliefert, um die Installation an Bord abzuschließen. Eine perfekte Antenne für Design und Konstruktion.

- ▶ Ideal for RIBs and small boats
- ▶ Foam injected - 100% WATERPROOF
- ▶ Anti - UV high gloss finish



Contents / Contenuto / Inhalt

1 x Antenna

1 x PL-259 (RG-58) male connector twist-on

Technical specifications

Frequency	156-162 MHz
Impedance	50 ohm
Electrical length	1/2 λ
V.S.W.R.	< 1,5:1
Polarization	Vertical
Gain	3 dB
Max power input	50 W
DC Ground	Yes
Whip material	Fiberglass
Ferrule	Reinforced nylon
Coaxial cable	5 m RG-58 CU MIL
Mounting	1" x 14 thread
Length	1,0 m (3.3')
Weight	0,39 kilo

(code: PF AN NVHF00001)

**5 YEAR
WARRANTY**

