



KS-42

3 dB VHF fiberglass antenna 2,4 m (8') length


 The classical 2,4 m (8') VHF marine antenna has been totally redesigned by Scout to set a new benchmark in terms of reliability and performance. The KS-42 is built with a heavy duty 1,5 mm thick fiberglass whip that gets fully foam injected with the special Scout 100% waterproof technique, and it's ice white colored with high gloss anti-UV filter to prevent color deterioration. Standard thread 1" x 14, chrome brass ferrule.

The antenna is supplied with 5m RG-58 MIL cable and 1 PL-259 connector to complete the installation on board. Suggested for medium and big size boats.

 La classica antenna nautica VHF da 2,4 m di lunghezza è stata completamente reinventata da Scout per fissare un nuovo standard di riferimento in termini di affidabilità e di prestazioni. La KS-42 è costruita con un corpo in vetroresina ad elevata resistenza con spessore di 1,5 mm interamente riempito di poliuretano con la speciale tecnica Scout 100% waterproof, e verniciata con tonalità bianco ghiaccio e filtro anti-UV per prevenire il deterioramento del colore ai raggi solari. Attacco standard 1" x 14 filetti in ottone cromato.

Viene fornita con 5m di cavo RG-58 top performance a norme militari e un connettore PL-259 per completare l'installazione a bordo.

Ideale per imbarcazioni di medie e grandi dimensioni.

 Die klassische 2,4 m (8') VHF-Marineantenne wurde von Scout völlig neu entworfen, um einen neuen Maßstab in Bezug auf Zuverlässigkeit und Leistung zu setzen. Die KS-42 hat einen 1,5mm Glasfaser Stab, der mit der speziellen 100% Waterproof Technik komplett schaumgefüllt ist, zusätzlich einen Hochglanz Anti UV- Filter, der die Farbe schützt. 1" Gewinde mit 14 Gewindengängen.

Die Antenne wird mit 5 m RG-58 MIL-Kabel und 1 PL-259-Stecker geliefert, um die Installation an Bord abzuschließen.

Ideal für mittlere und große Boote.

- ▶ Foam injected - 100% WATERPROOF
- ▶ Anti - UV high gloss finish



Contents / Contenuto / Inhalt

1 x Antenna

1 x PL-259 (RG-58) male connector twist-on

Technical specifications

Frequency	156-162 MHz
Impedance	50 ohm
Electrical length	1/2 λ
V.S.W.R.	< 1,5:1
Polarization	Vertical
Gain	3 dB
Max power input	50 W
DC Ground	Yes
Whip material	Fiberglass
Ferrule	Stainless steel
Coaxial cable	5 m RG-58 CU MIL
Mounting	1" x 14 thread
Length	2,4 m (8')
Weight	0,86 kilo

(code: PF AN NVHF00007)

**5 YEAR
WARRANTY**



Fitting with
mount PA-30