



KS-42 Blue Line

3 dB VHF fiberglass antenna 2,4 m (8') length - Blue

 The classic of VHF marine communication is now available in the new Blue Line colouring, specifically designed for the aesthetics of the most modern boats.


The KS-42 Blue Line is built with a heavy duty 1,5 mm thick fiberglass whip that gets fully foam injected with the special Scout 100% waterproof technique. Standard thread 1" x 14, chrome brass ferrule.

The antenna is supplied with 5m RG-58 MIL cable and 1 PL-259 connector to complete the installation on board. Suggested for medium and big size boats.

 Il top della produzione nautica Scout è ora disponibile nella nuova colorazione Blue Line, dedicata appositamente per l'estetica e il design delle imbarcazioni più moderne. La KS-42 Blue Line è costruita con un corpo in vetroresina ad elevata resistenza con spessore di 1,5 mm interamente riempito di poliuretano con la speciale tecnica Scout 100% waterproof. Attacco standard 1" x 14 filetti in ottone cromato.

Viene fornita con 5m di cavo RG-58 top performance a norme militari e un connettore PL-259 per completare l'installazione a bordo.

Ideale per imbarcazioni di medie e grandi dimensioni.

 Die Top-Antenne der Scout Marineproduktion ist jetzt auch erhältlich in der neuen Blue Line Farbe mit dem speziellen Look modernster Boote.

Die KS-42 Blue Line hat einen 1,5mm Glasfaser Stab, der mit der speziellen 100% Waterproof Technik komplett schaumgefüllt ist. 1" Gewinde mit 14 Gewindegängen.

Die Antenne wird mit 5 m RG-58 MIL-Kabel und 1 PL-259-Stecker geliefert, um die Installation an Bord abzuschließen. Ideal für mittlere und große Boote.

► Foam injected - 100% WATERPROOF

► Blue Line



Contents / Contenuto / Inhalt

1 x Antenna

1 x PL-259 (RG-58) male connector twist-on

Technical specifications

| | |
|-------------------|------------------|
| Frequency | 156-162 MHz |
| Impedance | 50 ohm |
| Electrical length | 1/2 λ |
| V.S.W.R. | < 1,5:1 |
| Polarization | Vertical |
| Gain | 3 dB |
| Max power input | 50 W |
| DC Ground | Yes |
| Whip material | Fiberglass |
| Ferrule | Stainless steel |
| Coaxial cable | 5 m RG-58 CU MIL |
| Mounting | 1" x 14 thread |
| Length | 2,4 m (8') |
| Weight | 0,86 kilo |

(code: PF AN NVHF00008)

**5 YEAR
WARRANTY**



Fitting with
mount PA-30