


QUICK 2


NEW

3 db VHF fiberglass antenna 1,5 m (5') length - QuickFit

 QuickFit is the brand-new line of ready-to-install marine antennas by Scout, that do not require the installation of RF connectors, easy to remove and totally waterproof thanks to the Scout original foam injection technology.

QuickFit antennas are built with FME type termination, they come with coax cables with pre-installed connectors and do not require any specific equipment or tools to make the installation on the boat, either on deck, rail or mast. Installation can be carried out easily as no technical skills are required.

The QUICK 2 antenna is built with a 1,4 mm thick fiberglass whip that gets fully foam injected with the special Scout 100% waterproof technique, and it's ice white colored with high gloss anti-UV filter to prevent color deterioration. A perfect antenna for its design and construction suitable for any type of motorboat.

 QuickFit è una nuovissima linea di antenne marine pronte per l'installazione che non richiedono il montaggio di connettori, facili da rimuovere e totalmente impermeabili grazie alla tecnologia Scout di iniezione poliuretano a cellule chiuse.

Le antenne QuickFit sono costruite con terminazione di tipo FME, vengono fornite unitamente a un cavo coassiale con connettori FME preinstallati e non necessitano di alcuna attrezzatura specifica per eseguire l'installazione sulla barca, sia che si tratti di una superficie orizzontale, in testa d'albero o su pulpito. Chiunque può facilmente installare l'antenna in autonomia, non essendo necessarie particolari competenze tecniche.

L'antenna QUICK 2 è costruita con un corpo in vetroresina con spessore di 1,4 mm interamente riempito di poliuretano con la speciale tecnica Scout 100% waterproof, e verniciata con tonalità bianco ghiaccio e filtro anti-UV per prevenire il deterioramento del colore ai raggi solari. Una antenna perfetta per concezione e costruzione adatta ad ogni tipo di imbarcazione a motore.

Contents / Contenuto / Inhalt


1 x Antenna
1 x 5 m RG-58 cable with FME female connectors
1 x adaptor FME male/PL-259 male

Technical specifications

Frequency	156-162 MHz
Impedance	50 ohm
Electrical length	1/2 λ
V.S.W.R.	< 1,5:1
Polarization	Vertical
Gain	3 dB
Max power input	50 W
DC Ground	Yes
Whip material	Fiberglass
Connector	FME male
Mounting	1" x 14 thread
Length	1,5 m (5')
Weight	0,50 kilo

(code: PF AN NVHF00034)

**5 YEAR
WARRANTY**



- ▶ Easy installation with pre-assembled FME connectors
- ▶ No tools required
- ▶ Great performance and durability
- ▶ Foam injected waterproof antenna